


# Panasonic

BUSINESS

MARCH 2019



System Camera and Switcher  
Product Lineup

As of March, 2019

For indoor use




**AW-HE130W**  
**AW-HN130K**

**AW-HE130K**  
**AW-HN130K**

1/2.86-type 3MOS	20x optical zoom	Digital Zoom
DRS/Hybrid DNR	OIS	PoE+
IP control	IP control	IP control
HD image IP transmission	Up to 100 presets	Audio Input

### Integrated pan-tilt full-HD cameras supporting IP transmission output of full-HD images

- Equipped with 1/2.86-type full-HD 3MOS sensors and DSP (Digital Signal Processor). Achieves high sensitivity, a high S/N ratio and high resolution through the use of advanced video processing.
- Supports HD/SD multi-format including 1080/29.97p<sup>\*5</sup>, 25p<sup>\*5</sup>, and 23.98p<sup>\*6</sup>.
- Optical Image Stabilization System (OIS) and 1.4x Digital Extender Zoom.
- Independent Color Correction Function with 12-axis Color + 3-axis Skin Tone and Color Temperature Adjustment Mode.
- Shoot clearer video with Hybrid Digital Noise Reduction (Hybrid DNR).
- Equipped with Night Mode for infrared shooting.
- The Freeze During Preset function enables to freeze the video during preset playback.
- In addition to HD-SDI and HDMI output, IP transmission of full-HD video output and multi-streaming output are supported.
- Transmit IP video without a separate encoder reduces cost and simplifies installation.
- Supports remote camera control using an IP control browser. It can be operated from not only a PC but also a MAC or mobile terminals.
- With PoE+<sup>\*3</sup>, power can be supplied via LAN cable so installation costs can be reduced.
- The AW-HN130W/K is a NDI I HX compatible model. It enables high-quality video to be encoded and transmitted in real-time and input signals to be directly sent to a switcher without the need for an IP decoder.
- The AW-HE130W/K can be upgraded to NDI I HX by purchasing a license<sup>\*4</sup>.



For indoor use



**AW-HE42W** **NEW**

**AW-HE42K** **NEW**

Scheduled for release in June 2019

Preliminary

1/2.3-type MOS	20x optical zoom	Digital Zoom/i.Zoom
DRS/DNR/HDR	OIS	PoE+
IP control	IP control	IP control
HD image IP transmission	Up to 100 presets	Audio Input
USB Video Class	MicroSD Card Recording	

### Integrated pan-tilt full-HD cameras supporting 3G-SDI output via HDMI, USB and IP transfer

- 1080/59.94p, 29.97p, 59.94i, 29.97PsF, 1080/50p, 25p, 50i, 25PsF, 720/59.94p and 50p video formats are supported.
- Ultra-high resolution technology with optical 20x zoom ensures high resolution at up to 30x zoom.
- Optical Image Stabilizer (OIS)/4-axis hybrid image stabilizer are equipped.
- Equipped with a four Drive Lens System where three zoom lenses and one focus lens independently operate simultaneously.
- Blown-out highlights and blocked-up shadows can be corrected with High Dynamic Range (HDR) mode.
- Night mode with automatic switching supports shooting in low-light locations.
- Equipped with a Freeze During Preset function that freezes video during preset playback.
- Full-HD video output is supported via IP transfer in addition to HDMI, SDI and USB output.
- Generator-lock function is equipped.
- The IP control browser supports camera control from remote locations. PC, Mac and mobile devices are supported.
- Power supply via a LAN cable is supported with PoE+. This reduces wires used and cost.
- External control of recording start/stop operations and transfer of saved files to an FTP server can be performed via an IP network.
- The AW-HE42W/K can be upgraded to NDI I HX by purchasing a license<sup>\*4</sup>.
- Equipped with a JPEG Image Saving function that enables camera video to be saved, played back and deleted on a microSD card as still JPEG images.

with software version 1.37 or earlier/AW-HE130W/K models with software version 2.22 or earlier/AW-HE40 series models with software version 1.67 or earlier/AW-HE38N/HK models with software version 1.67 or earlier) Contact your local Panasonic vendor for further information. \*5: Native output. \*6: Over 59.94i. \*7: A version software update may be required on the device.