



Professional SDI Video Switching that You Can Take Anywhere

- Support for SDI and HDMI cameras, smartphones, tablet computers and PCs etc.
- Easy to operate with hardware controls
- Compact size
- Supports up to Full HD 1080p
- 3 x 3G-SDI and 2 x HDMI*1 inputs
- 2 x 3G-SDI and 1x HDMI*1 output
- Input 4's scaler now supports a wider range of video and VESA resolutions.^{1,2}
- HDCP compliant
- Quad input multi-viewer with source labelling and audio metering
- Composition effects including DSK (Downstream Keyer), picture-in-picture etc.
- Capturing a still Image from Input Video on channel 4³ [Ver.1.5]
- Full 14-channel audio mixer included
- Software control using V-1SDI RCS application for Mac and PC and remote control via RS-232 connection
- Send a still image to the V-1SDI by V-1SDI RCS*3 [Ver.1.5]



SPECIFICATIONS V-1SDI

VIDEO	
Processing	4:2:2 (Y/Pb/Pr), 8-bit
Input Connectors	SDI INPUT 1--3: BNC x 3 * Conforms to SMPTE 424M (SMPTE 425M-AB), 292M HDMI INPUT 3--4: Type A (19 pins) x 2 * HDCP Supported * INPUT 3: SDI or HDMI selected.
Output Connectors	SDI OUT PGM: BNC x 1, SDI OUT PVW: BNC x 1 * Conforms to SMPTE 424M (SMPTE 425M-AB), 292M, HDMI OUT MULTI-VIEW: Type A (19 pins) x 1 * HDCP Supported
Input formats	SDI INPUT 1-3 Conforms to SMPTE 296M, SMPTE 274M HDMI INPUT 3 720/59.94p, 720/50p SMPTE 296M(FORMAT switch = 720p) 1080/59.94i, 1080/50i, 1080/59.94p, 1080/50p SMPTE 274M (FORMAT switch = 1080i or 1080p) * The input interlaced video signal is converted to progressive video signal by internal processing. * The video signal frame rate can be selected at the SETUP menu (59.94 or 50). HDMI INPUT 4 480/59.94i, 576/50i, 480/59.94p, 576/50p, 720/59.94p, 720/50p, 1080/59.94i, 1080/50i, 1080/59.94p, 1080/50p VGA (640 x 480/60 Hz), SVGA (800 x 600/60 Hz), XGA (1024 x 768/60 Hz) WXGA (1280 x 768/60 Hz), SXGA (1280 x 1024/60 Hz) FWXGA (1366 x 768/60 Hz), SXGA+ (1400 x 1050/60 Hz) UXGA (1600 x 1200/60 Hz), WUXGA (1920 x 1200/60 Hz) * The refresh rate is the maximum value of each resolution. * Conforms to VESA DMT Version 1.0 Revision 11. * 1920 x 1200/60 Hz: Reduced blanking. * The input interlaced video signal is converted to progressive video signal by internal processing. * The video signal frame rate can be selected at the SETUP menu (59.94 or 50).
OUTPUT formats	SDI OUT(PGM/PVW) Conforms to SMPTE 296M, 274M HDMI OUT MULTI-VIEW 720/59.94p, 720/50p SMPTE 296M(FORMAT switch = 720p) 1080/59.94i, 1080/50i SMPTE 274M(FORMAT switch = 1080i) 1080/59.94p, 1080/50p SMPTE 274M(FORMAT switch = 1080p) * The video signal frame rate can be selected at the SETUP menu (59.94 or 50).
Video Effects	Transition: CUT, MIX (DISSOLVE/FAM/NAM/MOSAIC), WIPE (30 types) Composition: PinP, SPLIT, QUAD, DSK (Luminance Key, Chroma Key)

AUDIO	
Audio Processing	Sampling rate: 24 bits/48 kHz
Audio formats	SDI: Linear PCM, 24 bits/48 kHz, 2ch Conforms to SMPTE 299M HDMI: Linear PCM, 24 bits/48 kHz, 2ch
Input Connectors	Digital: SDI INPUT 1--3 (BNC) x 3 SMPTE 299M HDMI INPUT 3--4 (HDMI Type A 19 pins) x 2 Analog: AUDIO IN (RCA phono type) MIC (Stereo mini type, plug-in power supported)
Output Connectors	Digital: SDI OUT PGM: BNC x 1 SMPTE 299M SDI OUT PVW: BNC x 1 SMPTE 299M HDMI OUT MULTI-VIEW: Type A (19 pins) x 1 Analog: AUDIO OUT (RCA phono type) PHONES (Stereo mini type)
Input Level	AUDIO IN: -10 dBu (Maximum: +8 dBu) MIC: -41-- -13 dBu (Maximum: -1 dBu)
Input Impedance	AUDIO IN: 15 k ohms, MIC: 10 k ohms
Output Level	AUDIO OUT: -10 dBu (Maximum: +8 dBu) PHONES: 92 mW + 92 mW (32 ohms)
Output Impedance	AUDIO OUT: 1 k ohm, PHONES: 10 ohms
Audio Effects	EQ, Delay, Compressor, HPF, Gate, Reverb, Mastering effect
OTHERS	
Other Connectors	USB: B Type (for remote control from PC), RS-232: DB-9 type
Other Functions	MEMORY (8 types), FREEZE (input video captured), OUTPUT FADE (Audio, Video: WHITE or BLACK)
Power Supply	AC Adaptor
Current Draw	2.1 A
Power Consumption	25 W
Operating Temp.	+0 to +40 degrees Celsius, +32 to +104 degrees Fahrenheit
Dimensions	313 (W) x 108 (D) x 59 (H) mm, 12-1/3 (W) x 4-1/4 (D) x 2-1/3 (H) inches
Weight (excl. AC adapt.)	1.2 kg, 2 lbs 10-2/5 oz
Accessories	Owner's manual, AC adaptor, Power cord, Cord hook